

Oval shelving module

Item.no IS-9416-1/2

Complete with:

- 1 post with feet,
- 2 top shelf,
- 1 bottom shelf,
- 2 Floating shelves (IS-9455)
- 1 table posts,
- 4 T-box connectors,
- 4 table feet.



Accessories



LED spotlights in bag
12V / 18 W incl. transformer
Item IS-SL-LED



Floating shelf, item IS-9455



Media screen holder
Small, item IS-9004
Must be used with a 90° inside curved beam.



Bag for table
Item IS-80-TB05



1 Screw in the 4 adjustable feet in the base plate so the height from the floor will be 22 mm/0,86".



2 Attach the base table to the module you built before and to the included base post.



3 Complete the posts with the extension and top post



4 Attach the table posts and lock the bottom FASTclamp



5 Attach the 2 T-box to the system with the magnetic tape outside from the table.



6 Attach the table top and lock the 2 FASTclamp's on the reverse side...



7 ...and the 2 FASTclamp,s at the posts, assemble the graphic panel above the tabletop.




8 Mount one of the top shelves upside down on the top of the graphic panel.



9 Attach the 2 T-box over the shelf with the magnetic tape outside from the table. Attach the graphic panels at the base and top and you are ready

Graphic panel production

Top graphic



Wall graphic





Table graphic



Graphic panel attachments



Accessories

Kickers & Hangers

800 mm / 31 1/2" Item: IS-800-KHN

Magnetic tape (not incl.)

12 mm / 0.5", Item: 82281
24 mm / 1", Item: 82282



Printer material

We recommend the following material:

Poster paper: 180 gr / 0.4 lb.

The printed graphic panels must be laminated before use.

Front side: 125 microns (0,125 mm) / 0.005" "deep crystal"

Reverse side: 250 microns (0,250 mm) / 0.010" "stop light"

Polyester film: 330-370 microns (0,350 mm) / 0.013-0.015"

Top laminate: 125 microns (0,125 mm) / 0.005" "deep crystal"

Mounting of Hangers

Hangers to be fixed at the top of the wall graphic panel (reverse side).

Mounting of Magnetic Tape

Magnetic tape to be fixed on the graphic panels. (See picture)

IMPORTANT Carefully mount the magnetic tape slightly inset from the edge of the graphic panel by approximately 0,25 mm / 0.010". Once mounted, a very thin straight white line should show between the edge of the graphic and the outside edge of the magnetic tape. Do not exceed 0,5 mm / 0.020".

Application Techniques

To obtain optimum adhesion, the bonding surfaces must be well unified, clean and dry. Typical surface cleaning solvents are isopropyl alcohol/water mixture (rubbing alcohol) or heptane.

Note: Be sure to follow solvent manufacturer's precautions and directions for use when using solvents.

